

Socket-Weld Flange

#600 • ASME B16.5 • NPS 1/2" to 24" • Dimensional Specifications

COMPANY

HEBEI YAJIADA IMPORT AND EXPORT CO., LTD

Founded 2008 • 50,000 T/YR annual capacity • Cangzhou, Hebei, China

hbyagada.com • mafuze@hebeiyagada.com • +86 186 3177 4440

NPS_n	FLANG	FLANG	Insid	Outsi	Bolt	Raise	Raise	H	D	ID 2*	Raise	T1	Flat	Bolt	No.
1/2	3/4	1.09"	eter	meter	e .69"	Face	Face	.44"	0.74"	1.63"	Face	1.38"	Thick	(B)	Bolt
1															
1-1/4	1-1/4"	1.70"	6.25"	4.38"	2.50"	.250"	2.50"	.56"	1.28"	1.88"	n	1.13"	1.63"	1.00"	4 -
1-1/2															
2	2"	2.44"	8.50"	6.50"	3.63"	.250"	4.13"	.69"	1.94"	2.50"	1.50"	2.25"	1.00"	8	-
2-1/2															

FLANGE TYPE

Socket-Weld Flange (1 1/2 2 2 1/2 3 3 1/2 4 4 1/2 6 8 10 12 14 16 18 20 22 24). Per ASME B16.5-2020 Table 7. Tolerances per ASME B16.5 §5.1 (typical 0.5mm/1mm). Hub length per ASTM A105 / A350 LF2 Cl.1 / A182 F304/F316 standard stock.