

Threaded Flange

#1500 • ASME B16.5 • NPS 1/2" to 24" • Dimensional Specifications

COMPANY

HEBEI YAJIADA IMPORT AND EXPORT CO., LTD

Founded 2008 • 50,000 T/YR annual capacity • Cangzhou, Hebei, China

hbyagada.com • mafuze@hebeiyagada.com • +86 186 3177 4440

NPS_no	FLANGE	FLANGE	Inside	Outsid	Bolt C	Raised	Raised	H	Raised	T1	Flat	Bolt	No.
1/2													
3/4	3/4"	1.14"	5.13"	5.98"	1.87"	.250"	1.75"	1.63"	1.00"	1.38"	0.75"	4	-
1													
1-1/4	1-1/4"	1.75"	6.25"	4.38"	2.50"	.250"	2.50"	1.88"	1.13"	1.63"	1.00"	4	-
1-1/2													
2	2"	2.50"	8.50"	6.50"	3.63"	.250"	4.13"	2.50"	1.50"	2.25"	1.00"	8	-
2-1/2													

FLANGE TYPE

Threaded Flange (1 2 3 4). Per ASME B16.5-2020 Table 7. Tolerances per ASME B16.5 §5.1 (typical 0.5mm/1mm). Hub length per ASTM A105 / A350 LF2 Cl.1 / A182 F304/F316 standard stock.