

Threaded Flange

#600 • ASME B16.5 • NPS 1/2" to 24" • Dimensional Specifications

COMPANY

HEBEI YAJIADA IMPORT AND EXPORT CO., LTD

Founded 2008 • 50,000 T/YR annual capacity • Cangzhou, Hebei, China

hbyagada.com • mafuze@hebeiyagada.com • +86 186 3177 4440

NPS_no	FLANGE	FLANGE	Inside	Outsid	Bolt C	Raised	Raised	H	Raised	T1	Flat	Bolt	No.
1/2	3/4"	1.14"	4.62"	5.125"	(BC)	(R)	(RF)	1.25"	Thickn	1.00"	Thickne	(B)	Bolt
1	1-1/4"	1.75"	5.25"	3.88"	2.50"	.250"	2.50"	1.37"	0.81"	1.12"	0.75"	4	-
1-1/2	2"	2.50"	6.50"	5.00"	3.62"	.250"	3.31"	1.69"	1.00"	1.44"	0.75"	8	-
2	2-1/2												

FLANGE TYPE

Threaded Flange (1 1/2 2 2-1/2). Per ASME B16.5-2020 Table 7. Tolerances per ASME B16.5 §5.1 (typical 0.5mm/1mm). Hub length per ASTM A105 / A350 LF2 Cl.1 / A182 F304/F316 standard stock.