

Weld Neck Flange

#900 • ASME B16.5 • NPS 1/2" to 24" • Dimensional Specifications

COMPANY

HEBEI YAJIADA IMPORT AND EXPORT CO., LTD

Founded 2008 • 50,000 T/YR annual capacity • Cangzhou, Hebei, China

hbyagada.com • mafuze@hebeiyagada.com • +86 186 3177 4440

NPS_no	Flange	Flange	Inside	Outsid	Bolt C	Raised	Raised	H	H1	Raised	T1	Flat F	Bolt H	No. of
3	4"	3.83"	11.50"	12.25"	8.12"	.250"	9.25"	4.50"	4.75"	1.75"	4.50"	1.25"	8	Holes
5	6"	5.76"	15.00"	16.00"	10.00"	.250"	10.00"	6.63"	6.88"	2.19"	5.50"	1.25"	12	-
8	10"	9.75"	21.50"	22.50"	12.75"	.250"	14.50"	10.75"	11.00"	2.75"	7.25"	1.50"	16	-
12	14"	13.00"	25.25"	26.25"	16.25"	.250"	17.75"	14.00"	14.25"	3.38"	8.38"	1.63"	20	-
16	18"	17.00"	31.00"	32.00"	21.00"	.250"	22.25"	18.00"	18.25"	4.00"	9.00"	2.00"	20	-
20	24"	23.00"	41.00"	42.00"	27.25"	.250"	29.50"	24.00"	24.25"	5.50"	11.50"	2.63"	20	-

FLANGE TYPE

Weld Neck Flange (). Per ASME B16.5-2020 Table 7. Tolerances per ASME B16.5 §5.1 (typical 0.5mm/1mm). Hub length per ASTM A105 / A350 LF2 Cl.1 / A182 F304/F316 standard stock.